

CAUTION
CONTAINS PARTS AND ASSEMBLIES SUSCEPTIBLE TO DAMAGE BY ELECTROSTATIC DISCHARGE (ESD)

MODIFICATION
HARDWARE
A B C D E F H
SOFTWARE
A B C D E F H

IS&S, 14 CFR Part 145 Repair Station #172R916X has performed an Altimeter Test and Inspection in accordance with 14 CFR Part 91.411 and Part 43, Appendix E to:

Altitude	58,000 FT	75
Date	1-12-05	
Serial No.	44213	

Tester

AIR DATA DISPLAY UNIT (ADDU)
PER FAA TSO-C106/AS392C TYPES I & II, TSO-C106/AS 8002, TSO-C88a/AS8003
RTCA/DO-178B LEVEL A

POWER: 28 VDC (PRI) 24 VDC (SEC)

RANGE
ALTITUDE: -1000 TO +53,000 FT
-305 TO +16,154 M
IAS: 60 TO 500 KNOTS
BARO: 22.00 TO 31.00 IN.HG
745 TO 1050 hPa
MACH: 0.1 TO 1.0

WEIGHT: 3 LBS / 1.36 KG
DO-160D ENV. CAT. [(A1)-]BAB[SB-]XXXDFSXBABA[WWW]M[XC3]XXX[AC20-138]

PART NO. 9D-80130-15 SERIAL NO. 44213
SW VDD NO. 7H-7 MFG DATE 0502

INNOVATIVE SOLUTIONS & SUPPORT EXTON, PA. 19341 USA
CAGE: 0EUW0