

INDICATOR, FLIGHT DIRECTOR

TYPE NO. 329B-7R-2 TSO C3b, C4c, C52a
DO-138 ENV CAT. GAPAAAXXXXXX
26 V AC 400 HZ -25 VA 5 V AC/DC -1.2 A
BANK 360° PITCH ±90°

WT **5.0** LB SER NO. **1538**

COLLINS PN 622-0836-**003**

Collins Avionics Division/Rockwell International
Cedar Rapids, Iowa 52406 USA

MCN 2407
J1

MOD 1 2 3 4 5 6 7 8
9 10 11 12 13 14 15 16 17 18 19
20 21 22 23 24 25 26 27 28 29 30
31 32 33 34 35 36 37 38 39 40 41
42 43 44 45 A B C D E F

A circular connector with a metal housing and a black plastic insert. The insert contains numerous pins, each labeled with a letter or number. The labels include: A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45. The connector is secured with four screws.