



CAUTION: DO NOT BLOW INTO THESE PORTS. USE STRAIGHT THREAD FITTINGS ONLY. USE PINS RET 1+.

INDICATOR, AIRSPEED (MACH) 40-320 KNOTS, 4 TO 85 MPH
AMETEK, Sellersville, PA
MEG P/N 10189G M00 M00
SERIAL NO. 10189G M00 M00
WEIGHT 1.6 LBS MAX
FAA TSO C2B
NP-405

5V

STATIC P

5V

INDICATOR, AIRSPEED (MACH) 40-320 KNOTS, 4 TO 85 MPH
AMETEK, Sellersville, PA
MEG P/N 10189G M00 M00
SERIAL NO. 10189G M00 M00
WEIGHT 1.6 LBS MAX
FAA TSO C2B
NP-405

CAUTION: DO NOT BLOW INTO THESE PORTS. USE STRAIGHT THREAD FITTINGS ONLY. USE PINS RET 1+.

INDICATOR, AIRSPEED (MACH) 40-320 KNOTS, 4 TO 85 MPH
AMETEK, Sellersville, PA
MEG P/N 10189G M00 M00
SERIAL NO. 10189G M00 M00
WEIGHT 1.6 LBS MAX
FAA TSO C2B
NP-405

or Price, Pictures and Availibilit

512 2718

Cessna

P/N C661063-0107

CAUTION: DO NOT BLOW IN THESE PORTS. USE STRAIGHT THREAD FITTINGS ONLY.

STATIC

P

USE PINS
1+, 2 RET



5V, 2 LAMPS

INDICATOR, AIRSPEED (MACH)
40-320 KNOTS, .4 TO .85 MACH
AMETEK, SELLERSVILLE, PA.

MFG P/N 10189G [REDACTED] H00 MOD [REDACTED]

SERIAL NO. [REDACTED] 224

WEIGHT: 1.6 LBS MAX

FAA TSO C2b

NP-405