

**FLIGHT  
EAGLE  
210 - MPH**

**GOODYEAR  
AIRCRAFT  
TIRES**

MADE IN USA

**16X4.4**

FLE 210 C DT NY TL

**301-722-045**

**10 - PR**

**ELESS**

1. TUBE ON THE SIDE/ALL

LEAN IN

3. EVITH DAMPED  
2. COHOL

4. DOT ON EVITH WHEEL  
5. IT IF INDICATED ON WHEEL

6. THAT WHEEL BOLTS ARE PROPERLY  
TIGHTENED FOR WHEEL

7. MANUFACTURER'S INSTRUCTIONS

8. INFLATE TIRE TO RATED PRESSURE

AFTER 12 HOURS STRETCH PERIOD, REINFLATE TO  
RATED INFLATION PRESSURE

### AIR RETENTION CHECK

IF PRESSURE HAS DROPPED MORE THAN 8 PERCENT IN  
THE FIRST 24 HOURS:

1. CHECK FOR LOOSE OR DEFECTIVE VALVE VALVE  
CORE OR SEAL

2. IF OK, DISASSEMBLE TIRE / WHEEL ASSEMBLY

3. CHECK WHEEL TO RING SEAL FOR CONDITION  
PROPER FIT AND LUBRICANT

4. INSPECT WHEEL FOR CRACKS, POROSITY, FUSE PLUG  
OR PRESSURE RELEASE PLUG LEAKAGE

PART NUMBER

