

English Field Aviation

PART #: 5119408-13

Description: Placard

Bin:

Warehouse: TDW

Received:

Serial Number:

Expiration:

Condition: New

LOT #: LT14-01599



Job Number
113907

P.O. Number
HA167432

Quantity
1

Part Number
5200023-21

Release
517451

AI0504
PLACARD

5200023-21

LOT

Order#-64564

Ser#
PL-354419

USE MAIN TANKS FOR TAKEOFF
LANDING & EMERGENCY WITH
AUXILIARY FUEL PUMPS ON.

A. USE FULL RICH MIXTURE AND
AUXILIARY FUEL PUMPS ON LOW
WHEN SWITCHING TANKS.

B. 100/130 GRADE AVIATION FUEL
MINIMUM.

1. OPERATE ON MAIN TANKS UNTIL
FUEL QUANTITY IS LESS THAN
120 LBS. PER TANK.

2. TRANSFER WING LOCKER FUEL
WHILE OPERATING ON MAIN
TANKS IN STRAIGHT AND
LEVEL FLIGHT ONLY.

3. TURN TRANSFER PUMPS OFF
WHEN LIGHTS ILLUMINATE.

4. USE FUEL CROSSFEED SYSTEM
TO BALANCE MAIN FUEL
QUANTITIES IF ONE WING LOCKER
TANK DOES NOT TRANSFER OR IF
A SINGLE WING LOCKER TANK
IS INSTALLED.

5. SWITCH TO AUXILIARY TANKS
WHEN FUEL IS AGAIN LESS THAN
120 LBS PER TANK.

TO EXTEND LANDING GEAR MANUALLY

1. PLACE GEAR SWITCH IN NEUTRAL.
2. PULL GEAR MOTOR CIRCUIT
BREAKER.
3. PULL OUT CRANK TO ENGAGE.
4. TURN CLOCKWISE TO EXTEND.
5. PUSH BUTTON AND STOW CRANK.