

SYLVANIA
OSRAM SYLVANIA
Danvers, MA

Made in China
For Service or
Technical Assistance
Call 1-800-LIGHTBULB

120-277V

QUICKTRONIC®
Professional Series


QUICK60+®
System Warranty

600Vdc, Voltage to Ground <600V
High Power Factor Sound Rated A Inherent Thermal Protection
UL Listed Class P, Type 1 - Outdoor
Min. Start Temp. See Chart (60°F/16°C for SS Lamps)
Complies with FCC 47 CFR Part 18, Non-Consumer No PCBs
Ballast à semiconducteur - Protection thermique inhérente
This class A RFLD complies with Canadian ICES-005
Ce DEPR de la classe A est conforme à la norme NMB-005 du Canada

QTP 1x32T8/UNV ISN-SC
1-Lamp Instant Start T8 Electronic Ballast
UNIVERSAL VOLTAGE 50/60Hz

LAMP TYPES	LINE CURRENT		Min. Start Temp.
	120V	277V	
1 x F032T8	0.26A	0.11A	-20°F/-29°C
1 x F026T8	0.21A	0.10A	-20°F/-29°C
1 x F017T8	0.15A	0.07A	-20°F/-29°C

Also suitable for "U" bend and SS equivalents



Ground Ballast Case
Lampholders must be shorted as per diagram
Install in accordance with National Electrical Code

