

 **CAUTION**
CONTAINS PARTS AND
ASSEMBLIES SUSCEPTIBLE TO DAMAGE BY
ELECTROSTATIC DISCHARGE (ESD)

MODIFICATION
HARDWARE
A B C D E F H
SOFTWARE
B C D E F H

IS&S, 14 CFR Part 145 Repair Station #172R916X has performed an Altimeter Test and Inspection in accordance with 14 CFR Part 91.411 and Part 43, Appendix E to:

Altitude	53,000 FT	
Date	1-28-05	457
Part No.	43249	Tester

AIR DATA DISPLAY UNIT (ADDU)
PER FAA TSO-C10b/AS392C TYPES I & II, TSO-C106/AS 8002, TSO-C88a/AS8003
RTCA/DO-178B LEVEL A

POWER:	28 VLC (PRI)	24 VLC (SEC)
RANGE		
ALTITUDE:	-1000 TO +53,000 FT -305 TO +16,154 M	IAS: 60 TO 500 KNOTS
BARO:	22.00 TO 31.00 IN.HG 745 TO 1050 hPa	MACH: 0.1 TO 1.0
WEIGHT:	3 LBS/	1.36 KG
DO-160D ENV. CAT. ((A1)-)BAB(SB-XXXXFSXBABA[WWW]M[XXC3]XXX[AC20-136])		
PART NO.	9D-80130-31	SERIAL NO. 43249
W/DD NO.	31-7	MFG DATE 10504
INNOVATIVE SOLUTIONS & SUPPORT, EXTON, PA. 19341 USA		
CAGE: 05		