



CAUTION
CONTAINS PARTS AND
ASSEMBLIES SUSCEPTIBLE TO DAMAGE BY
ELECTROSTATIC DISCHARGE (ESD)

MODIFICATION

HARDWARE

B C D E F H

SOFTWARE

B C D E F H

IS&S, 14 CFR Part 145 Repair Station #172R916X has performed an Altimeter Test and Inspection in accordance with 14 CFR Part 91.411 and Part 43, Appendix E to:

Altitude	53,000 FT	
Date	6-14-04	75
Serial No.	36993	Tester

AIR DATA DISPLAY UNIT (ADDU)

PER FAA TSO-C10b/AS392C TYPES I & II, TSO-C106/AS 8002, TSO-C88a/AS8003
RTCA/DO-178B LEVEL A

POWER: 28 VDC (PRI) 24 VDC (SEC)

RANGE

ALTITUDE: -1000 TO +53,000 FT -305 TO +16,154 M	IAS: 60 TO 500 KNOTS
BARO: 22.00 TO 31.00 IN.HG 745 TO 1050 hPa	MACH: 0.1 TO 1.0

WEIGHT: 3 LBS / 1.36 KG

DO-160D ENV. CAT. [(A1)-]BAB[SB-]XXXDFSBABA[WWW]M[XXC3]XXX[AC20-136]

PART NO. 9D-80130-16 SERIAL NO. 36993

SW VDD NO. 7B-7 MFG DATE 0426

INNOVATIVE SOLUTIONS & SUPPORT EXTON, PA. 19341 USA
CAGE: 0EUW0



FIG MODULE (INCOM

AL NO. 36901

NO. 3508-112 MOD 2

FA TSO-C10b AS392C

ADO-178B LEVEL A

[BAB[SB]XXXXFXXBA

XXXI AC20

CITATION

STC REQD STO

INNOVATIVE SOLUTION

EXTON, PA. 19341 USA

CAUTION! CONTAINS

ASSEMBLIES SUSCEPTIBLE

ELECTROSTATIC DISCHARGE